

Type No.	Equivalents	NATO Reference	Nominal Voltage	Nominal Capacity	Length		Width or Diameter		Height		Weight	Terminations
			V	Ah	mm	Inches	mm	Inches	mm	Inches	Grams	
L1.5-1481	R25-4 AD4		1.5	40.0	67.0	2.6	67.0	2.6	97.0	3.8	550	2 PIN SOCKET
L1.5-1492	R40 FLAG		1.5	40.0	-	-	68.0	2.7	171.0	6.7	790	SCREW
L1.5-1509	DS6		1.5	10.0	33.0	1.3	33.0	1.3	102.0	4.0	140	SCREW
L1.5-1523	'O' Cell		1.5	2.2	32.0	1.25	32.0	1.25	86.0	3.4	120	SCREW AND LEAD
L1.5-2103		6135-99-910-1103	1.5	20.0	67.0		35.0		114.3		270	8 PIN SOCKET
L1.5-2105		6135-99-910-1105	1.5	40.0	68.0	2.7	68.0	2.7	116.0	4.5	680	8 PIN SOCKET
L1.5-2131		6135-99-910-1131	1.5	0.9	-	-	20.0	0.8	59.0	2.3	35	BT
L1.5-2135	DS6	6135-99-910-1135	1.5	10.0	38.1 max.	1.5	38.1 max.	1.5	113.0 max.		150	SCREW
L1.5-2134	DS7	6135-99-910-1134	1.5	7.0	32.0 max.	1.25	32.0 max.	1.25	93.7 max.		140	SCREW AND LEAD
L1.3-2109		6135-99-910-1109	3.0	10.0	67.0	2.7	35.0	1.5	114.5	4.5	270	8 PIN SOCKET
L3-1518	P.O. No. 11	6135-99-104-6934	3.0	7.0	66.0	2.6	34.0	1.3	86.0	3.4	230	SCREW
L4.5-1084		6135-99-942-4394	4.5	7.0	103.0 max.	4.0	36.5 max.		87.3		360	SCREW
L4.5-1501	3R25 AD28		4.5	10.0	102.0 max.		35.0 max.		106.0 max.		410	2 PIN SOCKET
L4.5-1542	126		4.5	7.0	97.5		34.0		86.5		360	SCREW
L4.5-1560	481		4.5	20.0	110.0		65.0		160.0		820	SCREW
L6-1515	TD8		6.0	20.0	91.5		91.5		97.0		1050	2 PIN SOCKET
L6-1522	TD4		6.0	10.0	67.0	2.6	67.0	2.6	109.0	4.3	550	2 PIN SOCKET
HP992	4R25Y HP992		6.0	10.0	67.0 max.	2.6	67.0 max.	2.6	112.0 max.	4.4	560	SCREW
L6-1528	4R25-2 991		6.0	20.0	137.0	5.4	72.0		127.0		1150	SCREW
L6-2145	4R25X	6135-99-910-1145	6.0	10.0	67.0	2.6	67.0	2.6	108.0	4.25	560	SPRING
L7.5-1465	AD31		7.5	7.0	100.0	3.9	66.0	2.6	80.0		571	2 PIN SOCKET
L7.5-1503	AD38		7.5	0.9	60.0		43.0		60.0		200	2 PIN SOCKET
L7.5-1552	R1585		7.5	60.0	198.0		96.0		196.0		4250	SCREW
L9-1497	TWIN PP10		9.0+9.0	20.0	95.0		68.0		208.0	8.2	1620	TWIN 2 PIN SOCKET
L9-1508	W9		9.0	0.9	128.6 max.		24.6 max.		76.0 max.	3.0	295	WANDER PLUG
L12-1470	USA926		12.0	10.0	137.0	5.4	72.0		127.0		1150	SCREW
L12-1510	HP1		12.0	10.0	135.0	5.3	68.0	2.7	110.0	4.3	1050	2 PIN SOCKET
L13.5-1487			1.5, 3.0, 4.5, 9.0	20.0	219.0	7.9	101.0	4.0	120.0	4.7	2300	SCREW
L15-1559	10R25-36		13.5 15.0		-	-	315.0	12.4	470.0	18.5	50000	CABLE
L15-1551	10R40-2		15.0	360.0	-	-	292.0	11.5	170.0		15000	CABLE
L15-1554			15.0	80.0	292.0	11.5	292.0	11.5	270.0	10.6	50000	SCREW
L22.5-2148		6135-99-910-2148	22.5	0.6	87.3		51.5		66.9		400	FLYING LEADS
L40.5-1065	P.O. No. 2		40.5	0.9	189.0	7.4	69.0	2.7	78.0	3.0	950	SCREW
L45-1557	B104		45.0	6.0	116.0	4.6	44.0	1.7	133.0	5.2	1100	FLYING LEADS
L67.5-2123	45F40 B101	6135-99-910-1123	67.5	0.2	68.3		33.3		93.7	3.7	397	SNAP FASTENERS
L90-1507	P.O. No. 18		90.0	0.2	70.0	2.7	50.0	2.0	97.0	3.8	460	3 PIN SOCKET
L90-1520	B126		90.0	0.6	214.0	8.4	40.0		137.0	5.4	1300	3 PIN SOCKET
L120-1196	P.O. No. 21		48, 60, 72 108, 120	0.9	206.0		166.0		73.0		3174	WANDER PLUGS

continued on page 33

ZINC-CARBON BATTERIES continued

Type No.	Equivalents	NATO Reference	Nominal Voltage	Nominal Capacity	Length		Width or Diameter		Height		Weight	Terminations
			V	Ah	mm	Inches	mm	Inches	mm	Inches	Grams	
L4.5-2144		6135-99-910-1144	4.5	7.0	101.6		35.0		79.4	3.1	361	FLAT SPRING
L9-2146		6135-99-910-1146	1.5, 3.0, 4.5, 6.0, 9.0	0.9	128.6 max.		24.6 max.		76.2 max.	3.0	298	WANDER PLUGS
L90-2124		6135-99-910-1124	22.5, 45.0 67.5, 90.0	0.2	136.5	5.4	36.5		82.6		470	8 PIN SOCKET

Many other less common types are available. Please contact the South Shields Sales Office.

Air-Depolarised Batteries - *standard range*

Type No.	Equivalents	Nominal Voltage	Nominal Capacity	Length		Width or Diameter		Height		Weight	Terminations
		V	Ah	mm	Inches	mm	Inches	mm	Inches	Grams	
A1.4-1578		1.4	720	275	10.8	140	5.5	178.0	7.0	5000	FLYING LEADS
A1.4-1579	BR8639	1.4	180	165	6.5	128	5.0	63.0	2.5	1220	SCREW AND LEAD
A1.4-1394	AR40	1.4	90	-	-	64	2.5	171.0	6.7	608	SCREW AND LEAD
A1.4-1489	DS5, 'U'	1.4	45	53	2.1	53	2.1	140.0	5.5	400	SCREW AND LEAD
AD513	AS1	1.4	750	168	6.6	168	6.6	219.0	8.2	7000	SCREW AND LEAD
A1.4-1535	DS3	1.4	90	-	-	64	2.5	164.5	6.5	600	SCREW AND LEAD
A1.4-1536	DS1 AD511	1.4	200	111	4.3	111	4.3	210.0	8.3	1200	SCREW AND LEAD
A1.4-1537	DS3 AD512	1.4	385	111	4.3	111	4.3	210.0	8.3	1200	SCREW AND LEAD
A2.8-1490	P.O. No. 34 AD412	2.8	100	113	4.4	113	4.4	145.0	5.7	1590	SNAP FASTENERS
A5.6-941		5.6	90	135	5.3	135	5.3	165.0	6.5	2500	FLYING LEADS
A5.6-1517	AD516	5.6	50	113	4.4	113	4.4	145.0	5.7	1590	SNAP FASTENERS
A7-1545	KOLTEC. WHITE CAT.	7.0	90	-	-	165	6.5	180.0	7.0	2750	SCREW
A11.2-1580		11.2	90	265	10.4	135	5.3	165.0	6.5	4860	FLYING LEADS
A16.8-1581	AD12	16.8	50	225	8.8	170	6.7	145.0	5.7	4200	SNAP FASTENERS